DATASHEET

Danalock Danabridge

Connect your Danalock V3 smart lock to the Danabridge V3 and control and operate your Danalock from anywhere. Enjoy the added convenience of letting family members, friends and home service providers in – even when you're not at home. FLEXIBLE ACCESS CONTROL

www.saltosystems.com

TECHNICAL SPECIFICATION: **DANALOCK - DANABRIDGE (D0xB)**












TECHNICAL DATA:

Product dimensions: (Ø x D):	53 x 32mm
Weight (without batteries:	36 Gms
Material:	ABS.
Colour available:	White.
Power source:	USB power supply.
Encryption level:	AES 256 bit
Wifi compatibility:	Wi-Fi 802.11b/g/n
IP class:	Not suitable for outdoor use.
Certifications:	CE, FCC/IC, MIC.

TECHNICAL DRAWING:



ACCESS CONTROL FEATURES:

 nctio	nalities

Number of Danalock V3 per Danabridge:	2	
Remote openings:	•	
Live audit trail:	•	
Battery status report:	•	

ID TECHNOLOGIES:

Bluetooth Smart BLE:	•
Smartphone OS compatibility:	IOS 9 or higher
	Android 6.0 or higher

WIRELESS TECHNOLOGIES:

Bluetooth Smart -BLE :	•
Zigbee:	_
Z-Wave:	

PLATFORMS:

Host-based access control:

Smile - Selfprogrammable	
ROM:	_
SVN data-on-card:	_
SALTO BLUEnet:	_
SALLIS:	_

Cloud-based locking solution:

SALTO KS:	_
Danalock platform:	•

INCLUDED ACCESORIES:

USB power adaptor:	1
USB cable:	1



² Frecuencies depend on diferent hardware