
## **Batteries**

## **DATA SHEET**

NO MERCURY ADDED			
Description	Mercury & Cadmium Free Alkaline Manganese Battery, C Size		
Chemical System	Alkaline Manganese		
Nominal Voltage	1.5 Volts		
Nominal Dimensions	Refer to drawing		
Terminals	Protruded positive (+) and flat negative (-) contacts		
Jacket	Foil jacket		
Applications	All electronic devices, e.g. transistor radios, cassette recorders, toys, alarm clocks, lighting & torches, portable fans		
Ambient Temperature Range	Operation: -18°C ~ 50°C Recommended: 10°C ~ 25°C Storage: Not exceed 30°C		
Shelf Life	10 years		
Approx. Weight	70g		

Cross References:						
GP	JIS	IEC	Energizer	Duracell	Varta	
14AUP	LR14	LR14	E39	MN1400	4014	


## Discharge curve:



## Remarks

1) Store period before test shall be under 20±2°C, RH 55±20% within 30 days of manufacture.
2) Batteries shall not leak during the service life test before the end voltage reached.





/	min	max
Ø	24.9	26.2
Α	48.6	50.0
С	13.0	_
F	_	7.5
G	1.5	_

Dimension: mm

The information (subject to change without prior notice) contained in this document is for reference only and should not be used as a basis for product guarantee or warranty. For applications other than those described here, please consult your nearest GP Sales and Marketing Office or Distributors.